RCRA REVISION CHECKLIST 120 [REVISED]

Wood Preserving; Revisions to
Listings and Technical Requirements
57 FR 61492-61505
December 24, 1992

(RCRA Cluster III, Both HSWA and Non-HSWA provisions)

Note: This revision checklist terminates the June 13, 1991 (56 FR 27332, withdrawn Revision Checklist 91) administrative stay by amending the F032, F034, and F035 listings and by revising technical requirements for new drip pads. This checklist amends the impermeability requirement for existing drip pads, replacing it with a specific hydraulic conductivity standard. The stay promulgated February 18, 1992 (57 FR 5859, withdrawn Revision Checklist 101) no longer applies. (Note, the preamble to this rule refers to this stay as the February 6, 1992 administrative stay.) Facilities with existing drip pads must meet this new hydraulic standard before the compliance date set in this rule rather than the October 20, 1992 deadline set in that administrative stay. States that have adopted Revision Checklists 91 and 101 are encouraged to adopt Revision Checklist 120 as soon as possible. States that have not yet adopted previous Wood Preserving checklists are strongly encouraged to use the Consolidated Wood Preserving Checklist updated through December 31, 1992.

| | | | | STATE ANALOG IS: | | i | |
|-----|--|-----------------------|--------------------------|------------------|------------------------|------------------------|---------------------|
| | FEDERAL REQUIREMENTS | FEDERAL RCRA CITATION | ANALOGOUS STATE CITATION | EQUIV- ALENT | LESS STRIN- GENT | MORE STRIN- GENT | BROADER IN SCOPE |
| | PART 261 | - IDENTIFICATION AND | LISTING OF HAZARD | ous w | ASTE | | |
| | | SUBPART DLISTS OF | HAZARDOUS WASTE | S | | | |
| | HAZARDOUS WASTES F | ROM NON-SPECIFIC SOU | JRCES | | | | |
| †,1 | revise F032, F034, and F035 listings to read as follows: | 261.31(a)/table | | | | | |

| | | | | | STATE ANALOG IS: | | | S: |
|---|---|--|--|---|--|---|--|---------------------|
| FEDERAL REQUIREM | MENTS | FEDERAL RCRA CITATION | ANALOGOUS STATE CITA | ATION | EQUIV- ALENT | LESS STRIN- GENT | MORE STRIN- GENT | BROADEI IN SCOPE |
| Industry and EPA hazardous waste No. | | На | izardous waste | | | | | azard code |
| * | * | * | * * | | | * | | |
| F032 | residua plants t contam chapter wastes formula | waters (except those that have not colls, preservative drippage, and spent hat currently use or have previously inated wastes that have had the FOG or potentially cross-contaminated w (i.e., F034 or F035), and where the titions). This listing does not include vater from wood preserving processes | formulations from wood p used chlorophenolic form 32 waste code deleted in a vastes that are otherwise of generator does not resum K001 bottom sediment slu | oreservi ulations accorda currently ne or ini udge fro | ng proces s (except pance with § y regulated tiate use come the treatments | ses gene cotentially \$ 261.35 of d as haza of chlorop atment of | rated at cross- of this rdous | (T) |
| F034 | residua plants t | vaters (except those that have not come into contact with process contaminants), process (T) s, preservative drippage, and spent formulations from wood preserving processes generated at nat use creosote formulations. This listing does not include K001 bottom sediment sludge from the not of wastewater from wood preserving processes that use creosote and/or pentachlorophenol. | | | | | | () |
| F035 | residua plants t K001 b | waters (except those that have not c ls, preservative drippage, and spent hat use inorganic preservatives con ottom sediment sludge from the trea e and/or pentachlorophenol. | formulations from wood ptaining arsenic or chromiu | reservi ım. This | ng proces s listing do | ses gene es not in | rated at clude | (T) e |
| * | * | * | * * | | | * | | |
| remove the administrate stay addressed in F 1 of the 261.31 tab | ootnote | 261.31(a)/table | | | | | | |
| PART 264 - STAN | NDARDS | FOR OWNERS AND OPE STORAGE, AND DIS | | | OUS W | /ASTE | TREA | TMENT |
| | | SUBPART W | DRIP PADS | | | | | |
| APPLICABILITY | | | | | | | | |
| change "run-on" to off"; at end of para add sentence regard applicability of 264.573(b)(3) leak collection system requirement | igraph, ding | 264.570(a) | | | | | | |

| | | | | STATE A | ANALOG IS | S: |
|--|--------------------------------------|--------------------------|-----------------|------------------------|------------------------|---------------------|
| FEDERAL REQUIREMENTS | FEDERAL RCRA CITATION | ANALOGOUS STATE CITATION | EQUIV- ALENT | LESS STRIN- GENT | MORE STRIN- GENT | BROADER IN SCOPE |
| add new paragraph; Subpart W requirements not applicable to management of infrequent, incidental drippage in storage yards provided: | 264.570(c) | | | | | |
| | 264.570(c)(1) | | | | | |
| | 264.570(c)(1)(i) | | | | | |
| | 264.570(c)(1)(ii) | | | | | |
| owner or operator maintains and complies with a written contingency plan describing how owner or operator will respond immediately to discharge of infrequent and incidental drippage; at a minimum, what the contingency plan must describe | 264.570(c)(1)(iii) 264.570(c)(1)(iv) | | | | | |
| ASSESSMENT OF EXIST delete ", and must document the age of the drip pad to the extent possible, to document compliance with paragraph (b) of this section" | ING DRIP PAD INTEGRIT 264.571(a) | Y | | | | |

| | | | | | STATE A | ANALOG IS | : |
|---|---|-----------------------|--------------------------|-----------------|------------------------|------------------------|---------------------|
| | FEDERAL REQUIREMENTS | FEDERAL RCRA CITATION | ANALOGOUS STATE CITATION | EQUIV- ALENT | LESS STRIN- GENT | MORE STRIN- GENT | BROADER IN SCOPE |
| 3 | change "modifications will be" to "modifications are"; change "insufficient" to "in sufficient"; change "263.573" to "264.573"; delete "and must document the age of the drip pad to the extent possible"; delete "All upgrades, repairs, and modifications must be completed in accordance with the following:" | 264.571(b) | | | | | |
| 3 | | 264.571(b)(1) | | | | | |
| | | 264.571(b)(2) | | | | | |
| | remove subparagraphs | 264.571(b)(3) | | | | | |
| | DESIGN AND INSTALLA | TION OF NEW DRIP PAD | S | | | | |
| | insert "new" before "drip pads"; replace "all of the applicable requirements of §§ 264.573, 264.574 and 264.575 of this subpart." with "one of the following:" | 264.572 | | | | | |
| | add new subparagraph; all of the requirements of 264.573 (except 264.573(a)(4)), 264.574 and 264.575 | 264.572(a) | | | | | |
| | add new subparagraph; all of the requirements of 264.573 (except 264.573(b)), 264.574 and 264.575 | 264.572(b) | | | | | |

| | | | | | STATE ANALOG IS: | | | |
|---------------|--|-----------------------|--------------------------|-----------------|------------------------|------------------------|---------------------|--|
| | FEDERAL REQUIREMENTS | FEDERAL RCRA CITATION | ANALOGOUS STATE CITATION | EQUIV- ALENT | LESS STRIN- GENT | MORE STRIN- GENT | BROADER IN SCOPE | |
| | DESIGN AND OPERATIN | IG REQUIREMENTS | | | | | | |
| 4, 5, 6 | remove existing text designated as (a)(4) and note regarding administrative stay for existing drip pads; replace with subparagraph addressing hydraulic conductivity requirements; maintain surface free of cracks and gaps; sealing material must be chemically compatible with preservatives that contact pad; requirements apply to existing drip pads and drip pads of owners/operators electing to comply with 264.572(a) | 264.573(a)(4)(i) | | | | | | |
| | add new subparagraph; owner or operator must obtain and keep at the facility written assessment of drip pad certified by independent qualified registered engineer; assessment must attest to results of evaluation; assessment must be reviewed, updated and recertified annually; evaluation must document extent to which drip pad meets 264.573 (except 264.573(b)) design and operating standards | 264.573(a)(4)(ii) | | | | | | |

| | | | | | STATE A | ANALOG IS | : |
|---|---|-----------------------|--------------------------|-----------------|------------------------|------------------------|---------------------|
| | FEDERAL REQUIREMENTS | FEDERAL RCRA CITATION | ANALOGOUS STATE CITATION | EQUIV- ALENT | LESS STRIN- GENT | MORE STRIN- GENT | BROADER IN SCOPE |
| 7 | replace existing introductory sentence with: "If owner/operator elects to comply with \$ 264.572(b) instead of \$ 264.572(a), the drip pad must have:" | 264.573(b) | | | | | |
| | add new subparagraph; leakage collection system immediately above the liner designed, constructed, maintained and operated to collect leakage from below the drip pad; date, time and quantity of leakage collected must be documented in operating log | 264.573(b)(3) | | | | | |
| | replace "at least once every seven days" with "in a manner and frequency"; replace phrase addressing the types of cleaning techniques with phrase addressing proper management of residues and weekly inspections of entire drip pad surface; at end add new sentence requiring owner/operator to determine whether residues are hazardous under 262.11 and, if so, manage according to Parts 261-268, 270 and RCRA §3010 | 264.573(i) | | | | | |

| | | | STATE ANALOG IS: | | | : |
|----------------------|-----------------------|--------------------------|------------------|--------|--------|----------|
| | | | | LESS | MORE | |
| | | | EQUIV- | STRIN- | STRIN- | BROADER |
| FEDERAL REQUIREMENTS | FEDERAL RCRA CITATION | ANALOGOUS STATE CITATION | ALENT | GENT | GENT | IN SCOPE |

PART 265 - INTERIM STATUS STANDARDS FOR OWNERS AND OPERATORS OF HAZARDOUS WASTE TREATMENT, STORAGE, AND DISPOSAL FACILITIES

SUBPART W--DRIP PADS **APPLICABILITY** change "run-on" to "runoff"; delete comma after first occurrence of "1990"; delete "generated" after first occurrence of "operator has"; at end of paragraph, add sentence regarding applicability of 265.443(b)(3) leak collection system requirement 265.440(a) add new paragraph; Subpart W requirements not applicable to management of infrequent, incidental drippage in storage yards provided: 265.440(c) owner or operator 265.440(c)(1) maintains and complies with a written contingency 265.440(c)(1)(i) plan describing how owner or operator will respond to 265.440(c)(1)(ii) discharge of infrequent and incidental drippage; at a 265.440(c)(1)(iii) minimum, what the contingency plan must

265.440(c)(1)(iv)

describe

| | | | | | STATE A | ANALOG IS | : |
|---|---|-----------------------|--------------------------|-----------------|------------------------|------------------------|---------------------|
| | FEDERAL REQUIREMENTS | FEDERAL RCRA CITATION | ANALOGOUS STATE CITATION | EQUIV- ALENT | LESS STRIN- GENT | MORE STRIN- GENT | BROADER IN SCOPE |
| | ASSESSMENT OF EXIST | ING DRIP PAD INTEGRIT | Y | | | | |
| | delete "justify and" after "The evaluation must"; delete ", and must document the age of the drip pad to the extent possible, to document compliance with paragraph (b) of this section" | 265.441(a) | | | | | |
| 3 | add comma after first occurrence of "this subpart"; change "modifications will be" to "modifications are"; delete "and must document the age of the drip pad to the extent possible"; delete "," after "265.443 of this subpart"; delete comma after "qualified"; delete "All upgrades, repairs, and modifications must be completed in accordance with the following:" | 265.441(b) | | | | | |
| 3 | | 265.441(b)(1) | | | | | |
| | | 265.441(b)(2) | | | | | |
| | remove subparagraphs | 265.441(b)(3) | | | | | |
| | DESIGN AND INSTALLA | TION OF NEW DRIP PAD | S | | | | |
| | replace "all of the applicable requirements of §§ 265.443, 265.444 and 265.445 of this subpart." with "one of the following:" | 265.442 | | | | | |

| | | | | | STATE A | ANALOG IS | : | | |
|------|---|-----------------------|--------------------------|-----------------|------------------------|------------------------|---------------------|--|--|
| | FEDERAL REQUIREMENTS | FEDERAL RCRA CITATION | ANALOGOUS STATE CITATION | EQUIV- ALENT | LESS STRIN- GENT | MORE STRIN- GENT | BROADER IN SCOPE | | |
| | all of the applicable requirements of 265.443 (except 265.443(a)(4)), 265.444 and 265.445 | 265.442(a) | | | | | | | |
| | all of the applicable requirements of 265.443 (except 265.443(b)), 265.444 and 265.445 | 265.442(b) | | | | | | | |
| | DESIGN AND OPERATING REQUIREMENTS | | | | | | | | |
| 4, 8 | remove existing text designated as 265.443(a)(4) and remove two notes regarding administrative stays for new and existing drip pads; replace with new subparagraph regarding hydraulic conductivity requirements; maintain surface free of cracks and gaps; surface material must be chemically compatible with preservatives that contact pad; requirements apply to existing drip pads and drip pads of owners/operators electing to comply with 265.442(a) | 265.443(a)(4)(i) | | | | | | | |

| | | | | | STATE A | ANALOG IS | : |
|---|--|-----------------------|--------------------------|-----------------|------------------------|------------------------|---------------------|
| | FEDERAL REQUIREMENTS | FEDERAL RCRA CITATION | ANALOGOUS STATE CITATION | EQUIV- ALENT | LESS STRIN- GENT | MORE STRIN- GENT | BROADER IN SCOPE |
| 0 | add new subparagraph; owner or operator must obtain and keep at the facility a written assessment of drip pad certified by independent qualified registered engineer; assessment must attest to results of evaluation; assessment must be reviewed, updated and recertified annually; evaluation must document extent to which drip pad meets 265.443 (except 265.443(b)) design and operating standards | 265.443(a)(4)(ii) | | | | | |
| 9 | replace existing introductory sentence with "If an owner/operator elects to comply with § 265.442(b) instead of § 265.442(a), the drip pad must have:" | 265.443(b) | | | | | |
| | add new subparagraph; leakage collection system immediately above the liner designed, constructed, maintained and operated to collect leakage from below the drip pad for removal; date, time and quantity of leakage collected must be documented in operating log | 265.443(b)(3) | | | | | |

| | | | STATE ANALOG IS: | | | : |
|--|-----------------------|--------------------------|------------------|------------------------|------------------------|---------------------|
| FEDERAL REQUIREMENTS | FEDERAL RCRA CITATION | ANALOGOUS STATE CITATION | EQUIV- ALENT | LESS STRIN- GENT | MORE STRIN- GENT | BROADER IN SCOPE |
| replace "at least once every seven days" with "in a manner and frequency"; replace phrase addressing the types of cleaning techniques with phrase addressing proper management of residues and weekly inspections of entire drip pad surface | 265.443(i) | | | | | |

- For those States that did not adopt the June 13, 1991 administrative stay, the changes to these listings represent a narrowing of the F032, F034 and F035 listings. Thus, these changes are optional for States not adopting that administrative stay. Those States which adopted that administrative stay should remove the wording added by the stay and replace the wording with that shown in the December 24, 1992 rule and presented in this checklist.
- Only those States that added the stay to their code need to make this change.
- The <u>Federal Register</u> instructions for revising this paragraph are unclear. According to EPA, the last sentence of (b), which introduces the subparagraphs, is to be removed, as well as subparagraphs (b)(1), (2), and (3). A technical correction will be published in the <u>Federal Register</u> in the near future.
- The <u>Federal Register</u> does not clearly indicate that these notes regarding administrative stays are removed by this rule; according to EPA, they should be removed. A technical correction will be published in the <u>Federal Register</u> in the near future.
- There are two typographical errors in this paragraph in the <u>Federal Register</u>; in both occurrences, " $1x10^{-7}$ " should be " $1x10^{-7}$."
- Note that the <u>Federal Register</u> is in error. According to EPA, the last line of 264.573(a)(4)(i) should read "\\$ 264.572(b) instead of \\$264.572(a)" rather than "\\$264.572(a) instead of 264.572(b)." As written, the code contradicts what is said in the 264.572(a)&(b) requirements.
- There is an error in the <u>Federal Register</u> at 264.573(b). According to EPA, the phrase "§ 264.572(b) instead of § 264.572(a)" should be "§ 264.572(a) instead of § 264.572(b)." As currently written, the code contradicts the 264.572(a)&(b) requirements.
- Note that the <u>Federal Register</u> is in error. According to the last line of 265.443(a)(4)(i) should read "\$ 265.442(b) instead of \$ 265.442(a)" rather than "\$ 265.442(a) instead of \$ 265.442(b)". As written, the code contradicts what is said in the 265.442(a)&(b) requirements.

There is an error in the <u>Federal Register</u> at 265.443(b). According to EPA, the phrase "§ 265.442(b) instead of § 265.442(a)" should be "§ 265.442(a) instead of § 265.442(b)." As currently written, the code contradicts the 265.442(a)&(b) requirements.